

AMENDMENTS TO THE CLAIMS:

This listing of claims replaces all prior versions and listings of claims in the application:

LISTING OF CLAIMS:

1. (Currently Amended) An electrode for use with an electrochemical cell having a liquid electrolyte, the electrode comprising:  
  
~~(3), containing~~ channels ~~(2) in which an~~ that are capable of holding the liquid electrolyte ~~liquid may flow~~.
2. (Currently Amended) The electrode ~~according to~~ of claim 1, ~~which contains~~ further comprising a coated film (5), the coating (2) containing that defines the channels.
3. (Currently Amended) The electrode of claim 1 ~~according to claims 1 or 2,~~ wherein the channels ~~(2) are implemented in the form of~~ comprise grooves on a the surface of the electrode ~~(1)~~.
4. (Currently Amended) The electrode of claim 1 ~~according to one of claims 1 through 3,~~ wherein the channels ~~(2)~~ are embossed into the electrode ~~(1)~~.
5. (Currently Amended) The electrode of claim 1 ~~according to one of claims 1 through 3,~~ further comprising:

[[~~-~~]] ~~which contains a coated film on a surface of the electrode; (5) and~~

[[~~-~~]] wherein the channels comprise regions of the electrode that are not covered by the film (2) ~~are formed by uncoated partial regions of the film (5).~~

6. (Currently Amended) The electrode of claim 1 ~~according to one of claims 1 through 5~~, wherein at least one of the channels (2) ~~have~~ has a width (b) between 0.1mm and 1mm.

7. (Currently Amended) The electrode of claim 1 ~~according to one of claims 1 through 6~~, wherein at least one of the channels (2) ~~have~~ has a depth (t) between 10µm and 200µm.

8. (Currently Amended) The electrode of claim 1 ~~according to one of claims 1 to 7, which~~ wherein the electrode extends along a longitudinal direction and wherein the channels (2) run transversely to the longitudinal direction.

9. (Currently Amended) The electrode of claim 1 ~~according to one of claims 1 to 8~~, wherein the channels (2) ~~run essentially along equidistant~~ comprise substantially straight lines that are substantially parallel to one another and that have substantially same lengths.

10. (Currently Amended) The electrode of claim 1 ~~according to one of claims 1 to 7, which~~ wherein the electrode extends along a longitudinal direction and wherein the channels (2) run ~~diagonally~~ substantially diagonal to the longitudinal direction.

11. (Currently Amended) The electrode of claim 1 ~~according to one of claims 1 through 8,~~ wherein the channels are curved and substantially parallel to one another (2) ~~run along curved lines which are offset parallel to one another.~~

12. (Currently Amended) The electrode of claim 1 ~~according to one of claims 1 through 7 or 10,~~ wherein at least two of the channels (2) intersect ~~one another.~~

13. (Currently Amended) The electrode of claim 1 ~~according to one of claims 1 through 12, which contains~~ wherein the electrode comprises a metal film coated with carbon powder.

14. (Currently Amended) An electrode roll comprising: [[,]]  
~~wherein~~ multiple layers of electrodes (11, 12) ~~according to one of claims 1 through 13~~ are positioned one on top of another;  
wherein at least one of the multiple layers comprises channels that are capable of holding liquid electrolyte.

15. (Currently Amended) The electrode roll ~~according to~~ of claim 14, wherein  
the multiple layers of electrodes comprise two electrodes (11, 12) ~~according to one of~~  
~~claims 1 through 13 are~~ wound together up.

16. (Currently Amended) An electrochemical cell comprising:  
~~having~~ a liquid electrolyte; and (3), containing a roll (8) ~~according to one of~~  
~~claims 14 or 15~~  
multiple layers of electrodes positioned one on top of another;  
wherein at least one of the multiple layers comprises channels that hold the liquid  
electrolyte.

17. (Currently Amended) A method ~~for~~ of manufacturing ~~an~~ the electrode of  
claim 1, comprising:  
coating the electrode with a film;  
calendaring the electrode coated with the film at a temperature that exceeds a  
predefined temperature; and  
embossing the electrode following calendaring to form the channels  
~~according to one of claims 1 through 13, wherein the coated and not yet~~  
~~embossed electrode is calendared at a high temperature.~~

18. (Currently Amended) The method ~~according to~~ of claim 17, wherein ~~the~~

~~calendering of the electrode is integrated into the~~ is part of a winding process for  
manufacturing an electrode roll using the electrode.

19. (Currently Amended) A method ~~for~~ of manufacturing ~~an~~ the electrode of  
claim 1, comprising: according to one of claims 1 through 13,  
embossing the electrode;  
coating at least part of the electrode with activated carbon; and  
calendereing the electrode.

20. (Currently Amended) A method ~~for~~ of manufacturing ~~an~~ the electrode of  
claim 1 according to one of claims 1 through 13, comprising:  
~~wherein an electrode is provided by uniformly~~ coating an unembossed metal film  
with an activated carbon[[],]; and  
forming the channels (2) ~~are attached into~~ in the activated carbon layer ~~of the~~  
~~electrode while simultaneously suctioning off the scratched off coating.~~

21. (Currently Amended) The method ~~according to~~ of claim 20, wherein ~~the~~  
~~channels (2) are scratched with the aid of~~ forming comprises etching the channels in the  
activated carbon using a swinging tip.

22. (Currently Amended) A method ~~for~~ of manufacturing ~~an~~ the electrode of

Applicants : Werner Erhardt, et al.  
Serial No. : Not Yet Assigned  
Filed : Herewith  
Page : 9

Attorney's Docket No.: 14219-096US1  
Client's Ref.: P2003,0024USN

claim 1 according to one of claims 1 through 13, comprising:

~~wherein~~ covering regions of an unembossed metal film designated for the  
channels while ~~intended for producing channels (2) are covered cyclically during the~~  
coating of the unembossed metal film with activated carbon, ~~through which uncoated~~  
~~regions of the electrode arise and thus form the channels (2).~~